# NSN 5320-01-458-1217

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-458-1217



# Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 1.740 inches and 1.760 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.102 inches and 0.112 inches

#### Shank Diameter:

Between 0.3115 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.415 inches and 0.440 inches

#### Lubrication:

Cetyl alcohol

# End Application:

C17

#### Grip Length:

Between 1.245 inches and 1.255 inches

#### Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Thread Size:**

0.313 inches

#### **Product Name:**

Pin-rivet, threaded

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4967 assn standard single material response

#### Surface Treatment:

Aluminum

### Surface Treatment Specification:

Per hi-shear spec. 294 mfr ref single treatment response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-458-1217

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

