

View Online at <https://aerobasegroup.com/nsn/5320-01-458-1953>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.500 inches and 2.520 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.150 inches and 0.160 inches

**Width Between Flats:**

Between 0.183 inches and 0.190 inches

**Shank Diameter:**

Between 0.437 inches and 0.439 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.582 inches and 0.676 inches

**Grip Length:**

Between 1.870 inches and 1.880 inches

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

0.4375 inches

**Special Features:**

Hi-kote 1 aluminum coating per hi-shear spec.294 and cetyl alcohol lube per hi shear spec.305

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Per hi-shear spec. 294 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0