
# NSN 5320-01-458-1953

Pin-rivet - Page 1 of 2



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 2.500 inches and 2.520 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.150 inches and 0.160 inches

#### Width Between Flats:

Between 0.183 inches and 0.190 inches

# Shank Diameter:

Between 0.437 inches and 0.439 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.582 inches and 0.676 inches

# Grip Length:

Between 1.870 inches and 1.880 inches

#### Thready Qty Per Inch (tpi):

20

# Thread Size:

0.4375 inches

#### **Special Features:**

Hi-kote 1 aluminum coatingb per hi-shear spec.294 and cetyl alcohol lube per hi shear spec.305

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### **Surface Treatment:**

Aluminum

#### Surface Treatment Specification:

Per hi-shear spec. 294 mfr ref single treatment response

#### **Thread Series Designator:**

Unjf

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No



# NSN 5320-01-458-1953

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

