
# NSN 5320-01-458-1959

Pin-rivet - Page 1 of 2



# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 2.625 inches and 2.645 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.150 inches and 0.160 inches

### Width Between Flats:

Between 0.183 inches and 0.190 inches

#### Shank Diameter:

Between 0.437 inches and 0.439 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.582 inches and 0.676 inches

# Grip Length:

Between 1.995 inches and 2.005 inches

### Thready Qty Per Inch (tpi):

20

### Thread Size:

0.437 inches

### **Special Features:**

Hi-kote 1 aluminum coating per hi-shear.294 and cetyl alcohol lube per hi shear spec. 305

#### Material:

Titanium alloy uns r56400

### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### **Surface Treatment:**

Aluminum

### Surface Treatment Specification:

Per hi-shear spec. 294 mfr ref single treatment response

### **Thread Series Designator:**

Unjf

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No



# NSN 5320-01-458-1959

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

