

NSN 5320-01-458-2518 Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-458-2518 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.723 inches and 1.743 inches **Head Style:** Err-090 **Head Height:** Between 0.1309 inches and 0.1329 inches Width Between Flats: Between 0.197 inches and 0.217 inches **Shank Diameter:** Between 0.3740 inches and 0.3745 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.6862 inches and 0.6912 inches Lubrication: Cetyl alcohol **End Application:** C-17 **Grip Length:** 

Between 1.183 inches and 1.193 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

**Thread Size:** 

0.375 inches

**Countersink Angle:** 

100.0 degrees

**Product Name:** 

Pin rivet, threaded

Material:

Titanium alloy uns r56400

**Material Specification:** 

Ams 4967 assn standard single material response

**Surface Treatment:** 

Aluminum

**Surface Treatment Specification:** 

I-shear spec. No. 29 (hi-kote 1 only) mfr ref 6th treatment response

## NSN 5320-01-458-2518

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A528u0