

View Online at <https://aerobasegroup.com/nsn/5320-01-458-4016>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

1.607 inches

Head Style:

Crown countersunk less than 135 degrees

Head Height:

Between 0.1309 inches and 0.1329 inches

Width Between Flats:

Between 0.1582 inches and 0.1617 inches

Shank Diameter:

Between 0.3740 inches and 0.3745 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.672 inches and 0.684 inches

Lubrication:

Cetyl alcohol

End Application:

C-17a globemaster iii

Grip Length:

1.062 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.3750 inches

Countersink Angle:

100.0 degrees

Product Name:

Pin-riquet, threaded, 100 degrees fl crown rivet head

Material:

Titanium alloy uns r56400

Material Specification:

Ams4967 federal specification single material response or ams4928 federal specification single material response

Surface Treatment:

Aluminum and chromate

Surface Treatment Specification:

Dps 4.50-197 hi-kote 1 only mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0