
## NSN 5320-01-458-5023

Pin-rivet - Page 1 of 2





## Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 2.113 inches and 2.133 inches

## Head Style:

Straight pan

## **Head Height:**

Between 0.178 inches and 0.188 inches

### Shank Diameter:

Between 0.4490 inches and 0.4995 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.717 inches and 0.752 inches

#### Lubrication:

Cetyl alcohol

## End Application:

C-17a aircraft

## Grip Length:

Between 1.433 inches and 1.443 inches

## Thready Qty Per Inch (tpi):

20

## Thread Size:

0.500 inches

### **Product Name:**

Pin-rivet, threaded-protruding head

### Material:

Titanium alloy uns r56400

### **Material Specification:**

Ams 4967 assn standard single material response

#### Surface Treatment:

Aluminum

### Surface Treatment Specification:

Dps 4.50-197 (hi-kote 1 only) mfr ref single treatment response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-458-5023

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

