## NSN 5320-01-458-7792



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-458-7792 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.323 inches and 1.343 inches **Head Style:** Err-090 **Head Height:** Between 0.010 inches and 0.015 inches Width Between Flats: Between 0.122 inches and 0.142 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3898 inches and 0.3948 inches **Head Minor Diameter:** Between 0.375 inches and 0.388 inches **Countersink Height:** Between 0.0600 inches and 0.0625 inches Lubrication: Solid film and cetyl alcohol **End Application:** C-17 **Grip Length:** Between 0.933 inches and 0.943 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Countersink Angle:** 100.0 degrees **Product Name:** Pin-rivet, threaded Material: Titanium alloy uns r56400 **Material Specification:** Ams 4967 assn standard single material response or ams 4928 assn standard single material response

Unjf

**Thread Series Designator:** 

## NSN 5320-01-458-7792

Pin-rivet - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0