## NSN 5320-01-459-4542

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-459-4542 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.928 inches and 0.938 inches **Head Style:** Err-090 **Head Height:** Between 0.102 inches and 0.112 inches Width Between Flats: Between 0.160 inches and 0.180 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.472 inches and 0.505 inches Lubrication: Solid film or cetyl alcohol **End Application:** C-17 **Grip Length:** Between 0.433 inches and 0.443 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.3125 inches Material: Titanium alloy **Material Specification:** Ams 4967 assn standard single material response or ams 4928 assn standard single material response **Surface Treatment:** Aluminum **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-459-4542

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0