
# NSN 5320-01-459-4542

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.928 inches and 0.938 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.102 inches and 0.112 inches

## Width Between Flats:

Between 0.160 inches and 0.180 inches

#### Shank Diameter:

Between 0.3115 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

# Head Major Diameter:

Between 0.472 inches and 0.505 inches

# Lubrication:

Solid film or cetyl alcohol

# End Application:

C-17

## Grip Length:

Between 0.433 inches and 0.443 inches

## Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Thread Size:

0.3125 inches

## Material:

Titanium alloy

## Material Specification:

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

#### Surface Treatment:

Aluminum

## **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-459-4542

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

