NSN 5320-01-459-6171

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-459-6171

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 2.1975 inches and 2.2175 inches
Head Style:
Err-090
Head Height:
Between 0.200 inches and 0.210 inches
Width Between Flats:
0.3125 inches
Shank Diameter:
Between 0.5610 inches and 0.5615 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.842 inches and 0.877 inches
Lubrication:
Cetyl alcohol
End Application:
C-17
Grip Length:
Between 1.4325 inches and 1.4425 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
95000 pounds per square inch
Thread Size:
0.5625 inches
Special Features:
Rivet is also internally left hand threaded in 0.320 inch max, 0.3125-24 unjf-3b
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4967 assn standard single material response or ams 4928 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Per hi-kote 1, specification no. 294 mfr ref single treatment response
Thread Series Designator:

Unjf

NSN 5320-01-459-6171

Pin-rivet - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0