## NSN 5320-01-459-6179

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-459-6179



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 3.3225 inches and 3.3425 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.200 inches and 0.210 inches

#### Width Between Flats:

0.3125 inches

#### Shank Diameter:

Between 0.5610 inches and 0.5615 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.842 inches and 0.877 inches

## Lubrication:

Cetyl alcohol and solid film

## **End Application:**

C-17

## Grip Length:

Between 2.5575 inches and 2.5675 inches

## Thready Qty Per Inch (tpi):

18

## Min. Tensile Strength (psi):

95000 pounds per square inch

## Thread Size:

0.5625 inches

## **Special Features:**

Rivet is also internally left hand threaded in 0.320 inch max, 0.3125-24 unjf-3b

## Material:

Titanium alloy uns r56400

## Material Specification:

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-459-6179

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

