# NSN 5320-01-459-6218

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-459-6218



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 2.385 inches and 2.405 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.200 inches and 0.210 inches

### Width Between Flats:

0.3125 inches

#### Shank Diameter:

Between 0.5610 inches and 0.5615 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.842 inches and 0.877 inches

## Lubrication:

Cetyl alcohol

# End Application:

C-17

### Grip Length:

Between 1.620 inches and 1.630 inches

## Thready Qty Per Inch (tpi):

18

## Min. Tensile Strength (psi):

95000 pounds per square inch

## Thread Size:

0.5625 inches

#### **Special Features:**

Rivet is also internally left hand threaded in 0.320 inch max, 0.3125-24 unjf-3b

#### Material:

Titanium alloy uns r56400

## **Material Specification:**

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

#### Surface Treatment:

Aluminum

# Surface Treatment Specification:

Per hi-kote 1, specification no. 294 mfr ref single treatment response

## **Thread Series Designator:**

Unjf

# NSN 5320-01-459-6218

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

