

View Online at <https://aerobasegroup.com/nsn/5320-01-459-7257>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.5725 inches and 2.5925 inches

Head Style:

Err-090

Head Height:

Between 0.200 inches and 0.210 inches

Width Between Flats:

0.3125 inches

Shank Diameter:

Between 0.5610 inches and 0.5615 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.842 inches and 0.877 inches

Lubrication:

Cetyl alcohol

End Application:

C-17

Grip Length:

Between 1.8075 inches and 1.8175 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

95000 pounds per square inch

Thread Size:

0.5625 inches

Special Features:

Rivet is also internally left hand threaded in 0.320 inch max, 0.3125-24 unjf-3b

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Per hi-kote 1, specification no. 294 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0