NSN 5320-01-459-7299

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-459-7299 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 3.635 inches and 3.655 inches **Head Style:** Err-090 **Head Height:** Between 0.200 inches and 0.210 inches Width Between Flats: 0.3125 inches **Shank Diameter:** Between 0.5610 inches and 0.5615 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.842 inches and 0.877 inches Lubrication: Cetyl alcohol and solid film **End Application:** C-17 **Grip Length:** Between 2.870 inches and 2.880 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 95000 pounds per square inch **Thread Size:** 0.5625 inches **Special Features:** Rivet is also internally left hand threaded in 0.320 inch max, 0.3125-24 unjf-3b Material: Titanium alloy uns r56400 **Material Specification:** Ams 4967 assn standard single material response or ams 4928 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-459-7299

Pin-rivet - Page 2 of 2



Demi			

No

Fiig:

A528u0