

View Online at <https://aerobasegroup.com/nsn/5320-01-459-9398>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.385 inches and 2.405 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.200 inches and 0.210 inches

**Width Between Flats:**

0.3125 inches

**Shank Diameter:**

Between 0.5610 inches and 0.5615 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.842 inches and 0.877 inches

**Lubrication:**

Solid film and cetyl alcohol

**End Application:**

C-17

**Grip Length:**

Between 1.620 inches and 1.630 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

95000 pounds per square inch

**Thread Size:**

0.526 inches

**Special Features:**

Riuet is also internally left hand threaded in 0.320 inch max, 0.3125-24 unjf-3b

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A528u0