

View Online at <https://aerobasegroup.com/nsn/5320-01-460-0517>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.4475 inches and 2.4675 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.200 inches and 0.210 inches

**Width Between Flats:**

0.3125 inches

**Shank Diameter:**

Between 0.5610 inches and 0.5615 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.842 inches and 0.877 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

C-17

**Grip Length:**

Between 1.6825 inches and 1.6925 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

95000 pounds per square inch

**Thread Size:**

0.5625 inches

**Special Features:**

Rivet is also internally left hand threaded in 0.320 inch max, 0.3125-24 unjf-3b

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Per hi-kote 1, specification no. 294 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0