
# NSN 5320-01-460-2863

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 2.240 inches and 2.260 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.102 inches and 0.112 inches

### Width Between Flats:

Between 0.160 inches and 0.180 inches

#### Shank Diameter:

Between 0.3115 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.472 inches and 0.505 inches

### Lubrication:

Solid film and cetyl alcohol

### **End Application:**

C-17

Grip Length:

Between 1.745 inches and 1.755 inches

### Thready Qty Per Inch (tpi):

24

### Min. Tensile Strength (psi):

160000 pounds per square inch

### Thread Size:

0.3125 inches

### Material:

Titanium alloy

### Material Specification:

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

### Thread Series Designator:

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

# NSN 5320-01-460-2863

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

