## NSN 5320-01-460-3030

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-460-3030



### **Thread Class:** 3a **Thread Direction: Right-hand** Fastener Length: Between 1.365 inches and 1.385 inches Head Style: Flush countersunk Width Between Flats: Between 0.1270 inches and 0.1295 inches Shank Diameter: Between 0.3110 inches and 0.3120 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.6287 inches and 0.6335 inches Lubrication: Cetyl alcohol and solid film **End Application:** C-17 Grip Length: Between 0.870 inches and 0.880 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 210000 pounds per square inch

Thread Size:

0.3125 inches

Shear Strength:

19160 double pounds per square inch

#### Countersink Angle:

100.0 degrees

Material:

Nickel alloy 718

#### Material Specification:

Ams 5662 assn standard single material response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

# NSN 5320-01-460-3030

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

