## NSN 5320-01-460-8300

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-460-8300 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.4275 inches and 1.4475 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3640 inches and 0.3680 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.6862 inches and 0.6912 inches Lubrication: Cetyl alcohol **Grip Length:** Between 1.4225 inches and 1.4425 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4967 assn standard single material response or ams 4928 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Per hi-shear specification no 294 hi-kote 1 only mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-460-8300

Pin-rivet - Page 2 of 2



Fiig:

A528u0