# NSN 5320-01-461-2944

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-461-2944

# Fastener Length:

0.781 inches

### Head Style:

Flat chamfer

## Head Height:

Between 0.130 inches and 0.140 inches

## Shank Diameter:

0.250 inches

Shank Style:

Straight

#### Head Major Diameter:

Between 0.400 inches and 0.432 inches

### **Expansion Device:**

Serrated stem-type w

#### Grip Length:

Between 0.531 inches and 0.595 inches

#### Min. Tensile Strength (psi):

3650 pounds per square inch

### Shear Strength:

5900 single pounds per square inch

### **Product Name:**

Blind bolt fastener, high strength, pull-type, positive mechanical lock, protruding head

### Material:

Steel comp 8740 stem

### Surface Treatment:

Cadmium stem or aluminum stem

### Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification 1st treatment response sleeve or mil-c-83488 military specification 2nd treatment response sleeve

### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A040a0

## Mil-std (military Standard):

Mil-c-83488 spec.