# NSN 5320-01-462-2935

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-462-2935



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.760 inches and 0.780 inches

# Head Style:

Straight pan

#### **Head Height:**

Between 0.059 inches and 0.069 inches

#### Width Between Flats:

Between 0.094 inches and 0.096 inches

#### Shank Diameter:

0.249 inches

Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.387 inches and 0.412 inches

#### Lubrication:

Solid film or dry film and cetyl alcohol

# End Application:

F/a-18 e/f aircraft

# Grip Length:

0.375 inches

## Thready Qty Per Inch (tpi):

28

#### **Thread Size:**

0.250 inches

## Criticality Code Justification:

Agav

#### **Product Name:**

(inavy) pin-rivet, threaded, shear, protruding head, hex point drive, for sealant application

#### Material:

Stainless steel

#### **Material Specification:**

Ams 5629 assn standard single material response

# Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## **Thread Series Designator:**

Unjf

# NSN 5320-01-462-2935

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

