NSN 5320-01-462-7845

Blind Rivet - Page 1 of 1

Mil-c-5541 spec.



| View Online at https://aerobasegroup.com/nsn/5320-01-462-7845 |
|--|
| Fastener Length: |
| Between 0.440 inches and 0.460 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.188 inches and 0.192 inches |
| Shank Style: |
| Pin-rivet, straight, threaded |
| Head Major Diameter: |
| 0.357 inches |
| Expansion Device: |
| Serrated stem-type w |
| Grip Length: |
| Between 0.251 inches and 0.312 inches |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Steel comp 8740 stem |
| Material Specification: |
| Qq-a-430 federal specification single material response sleeve |
| Surface Treatment: |
| Cadmium stem and chromate stem |
| Surface Treatment Specification: |
| Qq-p-416, type 2, class 2 federal specification single treatment response stem |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |