

View Online at <https://aerobasegroup.com/nsn/5320-01-464-9241>

**Fastener Length:**

Between 1.075 inches and 1.125 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.063 inches and 0.070 inches

**Shank Diameter:**

Between 0.197 inches and 0.199 inches

**Shank Style:**

Collar and sleeve, self-plugging type

**Head Major Diameter:**

Between 0.396 inches and 0.416 inches

**Expansion Device:**

Break head

**Lubrication:**

Dry film or cetyl alcohol or paraffin wax

**Grip Length:**

Between 0.400 inches and 0.450 inches

**Special Features:**

Mscrow characteristics, material is a-286 per ams 5731, ams 5732 or ams 5737, heat treated to 175 ksi tensile, finish passivate per qq-p-35, kal gard ann-ro-1013 conversion coating optional; insert characteristics, material is acetal per astm 04181, no finish; drive nut characteristics, material is mild steel, color is brown; nut finish is kal gard ann-ro 1012 conversion coating or phosphate flouride per monogram specification ps741 may be used at mfg option

**Material:**

Titanium alloy nut

**Material Specification:**

Sae-ams 5639 assn standard 3rd material response sleeve

**Surface Treatment:**

Passivate sleeve

**Surface Treatment Specification:**

Sae-ams-qq-p-35 assn standard 3rd treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-t-9047 spec.