

View Online at <https://aerobasegroup.com/nsn/5320-01-464-9241>

Fastener Length:

Between 1.075 inches and 1.125 inches

Head Style:

Straight pan

Head Height:

Between 0.063 inches and 0.070 inches

Shank Diameter:

Between 0.197 inches and 0.199 inches

Shank Style:

Collar and sleeve, self-plugging type

Head Major Diameter:

Between 0.396 inches and 0.416 inches

Expansion Device:

Break head

Lubrication:

Dry film or cetyl alcohol or paraffin wax

Grip Length:

Between 0.400 inches and 0.450 inches

Special Features:

Mscrow characteristics, material is a-286 per ams 5731, ams 5732 or ams 5737, heat treated to 175 ksi tensile, finish passivate per qq-p-35, kal gard ann-ro-1013 conversion coating optional; insert characteristics, material is acetal per astm 04181, no finish; drive nut characteristics, material is mild steel, color is brown; nut finish is kal gard ann-ro 1012 conversion coating or phosphate flouride per monogram specification ps741 may be used at mfg option

Material:

Titanium alloy nut

Material Specification:

Sae-ams 5639 assn standard 3rd material response sleeve

Surface Treatment:

Passivate sleeve

Surface Treatment Specification:

Sae-ams-qq-p-35 assn standard 3rd treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-t-9047 spec.