# NSN 5320-01-465-7680

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-465-7680

Thread	Class:

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

1.045 inches

#### Head Style:

Err-090

## Head Height:

Between 0.078 inches and 0.088 inches

### Width Between Flats:

Between 0.1582 inches and 0.1617 inches

### Shank Diameter:

Between 0.3740 inches and 0.3745 inches

### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

Between 0.565 inches and 0.600 inches

### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

0.500 inches

## Thready Qty Per Inch (tpi):

24

## Thread Size:

0.375 inches

## Shear Strength:

125000 single pounds per square inch

# **Special Features:**

Light blue identification on top of head

## Material:

Nickel alloy 718

# Material Specification:

Ams 5662 assn standard single material response

# Surface Treatment:

Passivate

# Surface Treatment Specification:

Spec. 258, cagec 73197 mfr ref single treatment response

# Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-465-7680

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

