

View Online at <https://aerobasegroup.com/nsn/5320-01-465-9672>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

1.545 inches

Head Style:

Err-090

Head Height:

Between 0.120 inches and 0.135 inches

Width Between Flats:

Between 0.197 inches and 0.217 inches

Shank Diameter:

Between 0.364 inches and 0.368 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.565 inches and 0.600 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

1.000 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.375 inches

Material:

Steel

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or 6049 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty ii, cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.