# NSN 5320-01-465-9672

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-465-9672

Thread	Class:

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

1.545 inches

## Head Style:

Err-090

#### Head Height:

Between 0.120 inches and 0.135 inches

### Width Between Flats:

Between 0.197 inches and 0.217 inches

#### Shank Diameter:

Between 0.364 inches and 0.368 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.565 inches and 0.600 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

1.000 inches

## Thready Qty Per Inch (tpi):

24

# Min. Tensile Strength (psi):

160000 pounds per square inch

## Thread Size:

0.375 inches

## Material:

Steel

# Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or 6049 military

specification 3rd material response

## Surface Treatment:

Cadmium

# Surface Treatment Specification:

Qq-p-416, ty ii, cl 3 federal specification single treatment response

## **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

# NSN 5320-01-465-9672

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

