NSN 5320-01-466-3825

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-466-3825



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.9725 inches and 0.9925 inches

Head Style:

Err-090

Head Height:

Between 0.130 inches and 0.140 inches

Width Between Flats:

Between 0.1582 inches and 0.1617 inches

Shank Diameter:

Between 0.3735 inches and 0.3745 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.565 inches and 0.600 inches

Grip Length:

Between 0.3750 inches and 0.3850 inches

Min. Tensile Strength (psi):

21000 pounds per square inch

Thread Size:

0.375 inches

Shear Strength:

125000 single pounds per square inch

Material:

Nickel alloy 718

Material Specification:

Ms5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

258, cage 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-01-466-3825

Pin-rivet - Page 2 of 2

Fiig: A528u0

