NSN 5320-01-466-5226

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-466-5226

Identification Code Color:
Gray
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.2575 inches and 0.2595 inches
Head Major Diameter:
Between 0.378 inches and 0.385 inches
Expansion Device:
Threaded stem and expander
Lubrication:
Cetyl alcohol or carbo wax or paraffin wax
Grip Length:
Between 0.550 inches and 0.600 inches
Features Provided:
Drive nut
Min. Tensile Strength (psi):
2100 pounds per square inch
Shear Strength:
7900 double pounds per square inch
Countersink Angle:
Between 129.0 degrees and 131.0 degrees
Special Features:
Powder blast top of head
Heat Treatment:
Annealed sleeve
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Specification Data:
98524-mbf2113 manufacturers standard
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No

NSN 5320-01-466-5226

Blind Rivet - Page 2 of 2



Fiig:

A040a0