# NSN 5320-01-466-5796

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-466-5796

# Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

# Shank Diameter:

Between 0.1625 inches and 0.1645 inches

# Shank Style:

Threaded self-plugging shank w/sleeve

# Head Major Diameter:

Between 0.325 inches and 0.332 inches

# **Expansion Device:**

Threaded stem

Lubrication:

Dry film or cetyl alcohol or paraffin wax

# Grip Length:

Between 0.550 inches and 0.600 inches

#### **Countersink Angle:**

Between 129.0 degrees and 131.0 degrees

Material:

Titanium alloy uns r56400 nut

# **Material Specification:**

Mil-t-9047 military specification 1st material response nut or ams 4928 assn standard 2nd material response nut or ams 4967 assn standard

3rd material response nut

## Surface Treatment:

Passivate stem

#### **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A040a0

## Mil-std (military Standard):

Mil-t-9047 spec.