

View Online at <https://aerobasegroup.com/nsn/5320-01-467-2501>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Head Style:**

Err-090

**Head Height:**

Between 0.078 inches and 0.086 inches

**Width Between Flats:**

Between 0.127 inches and 0.129 inches

**Shank Diameter:**

Between 0.3260 inches and 0.3266 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.475 inches and 0.505 inches

**Lubrication:**

Cetyl alcohol or solid film

**End Application:**

E-3a

**Grip Length:**

Between 0.682 inches and 0.692 inches

**Thread Qty Per Inch (tpi):**

24

**Thread Size:**

0.312 inches

**Special Features:**

Name on standard is bolt, protruding head, hex drive, 95 ksi shear, 0.0156 inch oversize shank

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii, cl2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6758 spec.