

View Online at <https://aerobasegroup.com/nsn/5320-01-467-9002>

Thread Class:

3a

Thread Direction:

Right-hand

Identification Code Color:

Orange

Fastener Length:

0.763 inches

Head Style:

Flush countersunk

Shank Diameter:

Between 0.189 inches and 0.190 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.297 inches and 0.302 inches

Lubrication:

Cetyl alcohol and solid film

End Application:

Truck, fl (m10a)

Grip Length:

0.438 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

7060 double pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

End item strucassy, fcs; ultimate tension pounds 2.600; surface texture per ansi b46.1; curved or flat edge optional; shall have evidence of broken edge across points of hex socket

Material:

Nickel alloy 718

Material Specification:

Ams5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0