NSN 5320-01-467-9011



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-467-9011 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Orange **Fastener Length:** 1.013 inches **Head Style:** Flush countersunk **Shank Diameter:** Between 0.189 inches and 0.190 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.297 inches and 0.302 inches Lubrication: Cetyl alcohol and solid film **End Application:** Truck, fl (m10a) **Grip Length:** 0.688 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 7060 double pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** End item strucassy, fcs; ultimate tension punds 2.600; surface texture per ansi b46.1; curved or flat edge optional; shall have evidence of broken edge across points of hex socket Material:

Nickel alloy 718

Material Specification:

Ams5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

NSN 5320-01-467-9011

Pin-rivet - Page 2 of 2



She	lf	I if	ρ.
~	•••		•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0