## NSN 5320-01-467-9013

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-467-9013

View Online at https://aerobasegroup.com/nsn/5320-01-467-9013
Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Orange
Fastener Length:
1.200 inches
Head Style:
Flush countersunk
Shank Diameter:
Between 0.189 inches and 0.190 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.297 inches and 0.302 inches
Lubrication:
Cetyl alcohol and solid film
End Application:
Truck, fl (m10a)
Grip Length:
0.875 inches
Thready Qty Per Inch (tpi):
32
Thread Size:
0.190 inches
Shear Strength:
7060 double pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
End item strucassy, fcs; ultimate tension punds 2.600; surface texture per ansi b46.1; curved or flat edge optional; shall have evidence of
broken edge across points of hex socket
Material:
Nickel alloy 718
Material Specification:
Ams5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:

Unjf

## NSN 5320-01-467-9013

Pin-rivet - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0