

View Online at <https://aerobasegroup.com/nsn/5320-01-468-0829>

**Fastener Length:**

0.375 inches

**Head Style:**

Oval countersunk

**Shank Diameter:**

Between 0.155 inches and 0.159 inches

**Shank Style:**

Straight w/radius chamfered tip

**Head Major Diameter:**

Between 0.260 inches and 0.264 inches

**End Application:**

Aircraft, airlifter c-17a

**Countersink Angle:**

100.0 degrees

**Product Name:**

Rivet, solid, 100 degree flush crownrivet head

**Special Features:**

End item c-17a aircraft; surface texture 125 microinches ra maximum per ansi b46.1-78; deburr and break all edges .005-.015; head cocking angle of rivet head relative to axis of rivet 1/2 ; closed die configuration required; no sharp edges or burrs on rivet; rivet shall drive as recieved to 1.6xdiameter of rivet without cracking

**Material:**

Aluminum alloy 7050

**Material Specification:**

Qq-a-430, t73 federal specification single material response

**Surface Treatment:**

Anodize and aluminum

**Surface Treatment Specification:**

Mil-a-8825, type1, class1 military specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8825 spec.