

View Online at <https://aerobasegroup.com/nsn/5320-01-468-3333>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

1.263 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.064 inches and 0.074 inches

**Width Between Flats:**

Between 0.079 inches and 0.081 inches

**Shank Diameter:**

Between 0.189 inches and 0.190 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.357 inches and 0.377 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corporation and solid film

**End Application:**

B 2 bomber3

**Grip Length:**

0.938 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Shear Strength:**

125000 single pounds per square inch

**Product Name:**

Pin, threaded, hex point drive, protruding tension head, cres

**Special Features:**

parts should have a dark green dye on the chamfer area indicated; coverage shall not extend beyond the first two threads and shall be of the type that be removed with normal cleaning solvents; shall have evidence of broken edge across points of hex socket; surface texture per ansi b46.1

**Material:**

Nickel alloy 718

**Material Specification:**

Ams5662 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0