

View Online at <https://aerobasegroup.com/nsn/5320-01-468-3333>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

1.263 inches

Head Style:

Err-090

Head Height:

Between 0.064 inches and 0.074 inches

Width Between Flats:

Between 0.079 inches and 0.081 inches

Shank Diameter:

Between 0.189 inches and 0.190 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.357 inches and 0.377 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corporation and solid film

End Application:

B 2 bomber3

Grip Length:

0.938 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

125000 single pounds per square inch

Product Name:

Pin, threaded, hex point drive, protruding tension head, cres

Special Features:

parts should have a dark green dye on the chamfer area indicated; coverage shall not extend beyond the first two threads and shall be of the type that be removed with normal cleaning solvents; shall have evidence of broken edge across points of hex socket; surface texture per ansi b46.1

Material:

Nickel alloy 718

Material Specification:

Ams5662 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0