NSN 5320-01-468-5668

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-468-5668

Thread Direction:

Right-hand

Identification Code Color:

Black

Fastener Length:

Between 46.40 millimeters and 46.90 millimeters

Head Style:

Err-090

Head Height:

Between 1.15 millimeters and 1.40 millimeters

Width Between Flats:

Between 2.01 millimeters and 2.05 millimeters

Shank Diameter:

Between 4.965 millimeters and 4.990 millimeters

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 7.65 millimeters and 8.15 millimeters

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

Helicopter, eh101

Grip Length:

Between 38.87 millimeters and 39.13 millimeters

Thread Size:

5.0 millimeters

Thread Pitch In Millimeters:

0.80

Thread Tolerance Class:

4h external

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

294, cagec 73197 mfr ref single treatment response

Thread Series Designator:

Μ

Shelf Life:

N/a



NSN 5320-01-468-5668

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

