## NSN 5320-01-468-5975



Blind Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-468-5975 **Fastener Length:** 0.888 inches **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.197 inches and 0.199 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** 0.386 inches **Expansion Device:** Serrated stem-type w **End Application:** Aircraft, f-16 **Grip Length:** Between 0.469 inches and 0.532 inches **Hardness Rating:** 48.0 rockwell c stem and 53.0 rockwell c stem **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Fasterner, blind, high strengthpull type, positive mechanical lock, 100 degree flush head **Special Features:** Installed with single action tool Material: Stainless steel stem **Material Specification:** Astm-a-331 assn standard single material response stem **Surface Treatment:** Cadmium stem and aluminum stem **Surface Treatment Specification:** Qq-p-416, type2, class2 federal specification single treatment response sleeve or mil-c-83488 military specification single treatment response sleeve Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-c-83488 spec.