# NSN 5320-01-468-5982

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-468-5982

# Fastener Length:

0.855 inches

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

## Shank Diameter:

Between 0.162 inches and 0.164 inches

## Head Major Diameter:

0.333 inches

#### **Expansion Device:**

Serrated stem-type w

### **End Application:**

Aircraft f-16

### Grip Length:

Between 0.156 inches and 0.220 inches

### Hardness Rating:

48.0 rockwell c stem and 53.0 rockwell c stem

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

### **Product Name:**

Fasterner, blind, high strengthpull type, positive mechanical lock, 100 degree flush head

## **Special Features:**

Installed with single action tool

## Material:

Stainless steel stem

## **Material Specification:**

Astm-a-331 assn standard single material response stem

## Surface Treatment:

Cadmium stem and aluminum stem

## Surface Treatment Specification:

Qq-p-416, type2, class2 federal specification single treatment response sleeve or mil-c-83488 military specification single treatment response sleeve

## Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A040a0

## Mil-std (military Standard):

Mil-c-83488 spec.