NSN 5320-01-468-6013

Blind Rivet - Page 1 of 1

Mil-c-83488 spec.



View Online at https://aerobasegroup.com/nsn/5320-01-468-6013

Fastener Length:
0.855 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.162 inches and 0.164 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
0.333 inches
Expansion Device:
Serrated stem-type w
End Application:
Aircraft, f-16
Grip Length:
Between 0.406 inches and 0.470 inches
Hardness Rating:
48.0 rockwell c stem and 53.0 rockwell c stem
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
Fasterner, blind, high strengthpull type, positive mechanical lock, 100 degree flush head
Special Features:
Installed with single action tool
Material:
Stainless steel stem
Material Specification:
Astm-a-331 assn standard single material response stem
Surface Treatment:
Cadmium stem and aluminum stem
Surface Treatment Specification:
Qq-p-416, type2, class2 federal specification single treatment response sleeve or mil-c-83488 military specification single treatment response
sleeve
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):