

View Online at <https://aerobasegroup.com/nsn/5320-01-468-6292>

Fastener Length:

0.405 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.162 inches and 0.164 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.333 inches

Expansion Device:

Serrated stem-type w

End Application:

Morter, m-29

Grip Length:

Between 0.219 inches and 0.282 inches

Min. Tensile Strength (psi):

1350 pounds per square inch

Hardness Rating:

48.0 rockwell c stem and 53.0 rockwell c stem

Shear Strength:

2340 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Product Name:

Fastener, blind, high strenght, pull type, positive mechanical lock, 100 degree flush head, alloy steel

Special Features:

F16 aircraft

Material:

Steel sleeve

Material Specification:

Astma331 assn standard single material response stem

Surface Treatment:

Cadmium stem

Surface Treatment Specification:

Qq-p-416, type2, class2 federal specification single treatment response sleeve or mil-c-83488 military specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-f-81177 spec.