NSN 5320-01-468-8154

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-468-8154 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.928 inches and 0.948 inches **Head Style:** Err-090 **Head Height:** Between 0.068 inches and 0.078 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.475 inches and 0.505 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.433 inches and 0.443 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Special Features:** Threads modified on pin to 0.3020/0.3060 in. Dia; pin is 6al-4v alloy; collar is dyed red; washer is dyed grey or blue (for 2024 only) Material: Titanium alloy bolt **Material Specification:** Qq-a-430 federal specification single material response collar or qq-a-225/6 federal specification single material response collar **Surface Treatment:** Anodize washer **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response washer **Thread Series Designator:** Unjf Shelf Life:

--

N/a

Unit Of Measure:

NSN 5320-01-468-8154

Pin-rivet - Page 2 of 2



Demi			

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.