

View Online at <https://aerobasegroup.com/nsn/5320-01-468-8154>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.928 inches and 0.948 inches

Head Style:

Err-090

Head Height:

Between 0.068 inches and 0.078 inches

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3115 inches and 0.3120 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.475 inches and 0.505 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.433 inches and 0.443 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.312 inches

Special Features:

Threads modified on pin to 0.3020/0.3060 in. Dia; pin is 6al-4v alloy; collar is dyed red; washer is dyed grey or blue (for 2024 only)

Material:

Titanium alloy bolt

Material Specification:

Qq-a-430 federal specification single material response collar or qq-a-225/6 federal specification single material response collar

Surface Treatment:

Anodize washer

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response washer

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.