

View Online at <https://aerobasegroup.com/nsn/5320-01-468-8154>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.928 inches and 0.948 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.068 inches and 0.078 inches

**Width Between Flats:**

Between 0.1270 inches and 0.1295 inches

**Shank Diameter:**

Between 0.3115 inches and 0.3120 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.475 inches and 0.505 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.433 inches and 0.443 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.312 inches

**Special Features:**

Threads modified on pin to 0.3020/0.3060 in. Dia; pin is 6al-4v alloy; collar is dyed red; washer is dyed grey or blue (for 2024 only)

**Material:**

Titanium alloy bolt

**Material Specification:**

Qq-a-430 federal specification single material response collar or qq-a-225/6 federal specification single material response collar

**Surface Treatment:**

Anodize washer

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response washer

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-a-8625 spec.