NSN 5320-01-468-8196


Pin-rivet - Page 1 of 2

3a

32

Unjf

N/a





Thread Class: Thread Direction: Right-hand Identification Code Color: Violet, purple **Fastener Length:** Between 0.853 inches and 0.873 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches Shank Diameter: Between 0.1885 inches and 0.1895 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.357 inches and 0.377 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** A109 vehicle Grip Length: Between 0.433 inches and 0.443 inches Thready Qty Per Inch (tpi): **Thread Size:** 0.1825 inches Material: Steel **Material Specification:** Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response Surface Treatment: Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:** Shelf Life:

NSN 5320-01-468-8196

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

