## NSN 5320-01-469-1481

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-469-1481 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** 0.512 inches **Head Style:** Straight pan **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.079 inches and 0.080 inches **Shank Diameter:** Between 0.157 inches and 0.159 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.357 inches and 0.377 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.187 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.190 inches **Special Features:** 0.325 inch thread on stub end; head protrudes 0.187 inches on pin grip end Material: Titanium alloy uns r56400 **Material Specification:** Ams 4296 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5320-01-469-1481

Pin-rivet - Page 2 of 2



Fiig:

A528u0