NSN 5320-01-469-1481

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-469-1481

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

0.512 inches

Head Style:

Straight pan

Head Height:

Between 0.064 inches and 0.074 inches

Width Between Flats:

Between 0.079 inches and 0.080 inches

Shank Diameter:

Between 0.157 inches and 0.159 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.357 inches and 0.377 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.187 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.190 inches

Special Features:

 $0.325 \ \text{inch}$ thread on stub end; head protrudes $0.187 \ \text{inches}$ on pin grip end

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4296 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-01-469-1481

Pin-rivet - Page 2 of 2

Fiig: A528u0

