

View Online at <https://aerobasegroup.com/nsn/5320-01-469-2859>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.815 inches and 0.835 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.345 inches and 0.352 inches

Lubrication:

Solid film and cetyl alcohol

End Application:

F18 e/f

Grip Length:

Between 0.495 inches and 0.505 inches

Thread Qty Per Inch (tpi):

32

Thread Size:

0.1900 inches

Countersink Angle:

100.0 degrees

Product Name:

Pin, rivet, threaded-tension, 100 degree c'sunk head, hex point drive

Special Features:

Head surface coated with white paint number 37875 fed-std-595 removable with mek wipe

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

St3-760 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0